ANDERSON
Fibre Optic Manufacturing Excellence

rapidconnect Deployable Drums = RCDD-OD (outside diameter)

Type	RCDD-450							
Dimension	470×510×570mm（height）							
Drum OD	ϕ450mm							
Axle OD	ϕ200mm							
Width	290mm							
Packing size	505×550×600mm Polywood case							
Gross Weight	21.7KGS							
Net Weight	10.2KGS							
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm	
Capacity 3600M	2000M	1200M	900M	650M	500M	400M	320M	
Remarks	all-metal，Portable tie rod，wear-resistant rubber wheel，parking brake（army green and black available）							

Type	RCDD-430						
Dimension	430×360（includding handle）×460mm（H）						
Drum OD	ϕ430mm						
Axle OD	ϕ180mm						
Width	175mm						
Packing Dimension	470×380×510mm Carton						
Gross Weight	6KGS						
Net Weight	4.8KGS						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity 1000M	500M	400M					
Remarks	Plastic+Metal，Portable tie rod，wear-resistant rubber wheel						

Type	RCDD-350							
Dimension	420×375×454mm（height）							
Drum OD	ϕ350mm							
Axle OD	ϕ150mm							
Width	260mm							
Packing Dimension	515×505×520mm Polywood case							
Gross Weight	18.5KGS							
Net Weight	7.5KGS							
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm	
Capacity 1800M	1000M	600M	450M	320M	250M	200M	160M	
Remarks	all-metal，Portable tie rod，wear-resistant rubber wheel，parking brake（army green and black available）							

Type	RCDD-440						
Dimension	345*265*525mm						
Drum OD	ϕ440mm						
Axle OD	ϕ200mm						
Width	205mm						
Packing Dimension	460*400*530mm Carton						
Gross Weight	9.6KGS						
Net Weight	8.5KGS						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity 1200M	900M	600M	420M				
Remarks	Plastic+Metal，Portable tie rod，wear-resistant rubber wheel						

Type	RCDD-280						
Dimension	280×270（with handle）×380mm（H）						
Drum OD	ϕ280mm						
Axle OD	ϕ112mm						
Width	120mm						
Packing Dimension	345×280×450mm Carton						
Gross Weight	3.1KGS						
Net Weight	2.3KGS						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity 270M	160M	100M	65M				
Remarks	all-metal，handle，No wear-resistant rubber wheel						

Type	RCDD-235						
Dimension	232*195*315mm						
Drum OD	ϕ235mm						
Axle OD	ϕ137mm						
Width	110mm						
Packing Dimension	255*220*345mm Carton						
Gross Weight	1.6KGS						
Net Weight	1.2KGS						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity 269M	160M	97M	67M	49M	38M		
Remarks	Plastic，Portable tie rod，No wear-resistant rubber wheel						

Type	RCDD-312						
Dimension	292*240.5*391.7mm						
Drum OD	ϕ312mm						
Axle OD	ϕ176mm						
Width	135mm						
Packing Dimension	365*295*425mm Carton						
Gross Weight	3.3KGS						
Net Weight	1.8KGS						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity 628M	350M	226M	157M	115M	88M	70M	57M
Remarks	Plastic，Portable tie rod，No wear-resistant rubber wheel						

Type	RCDD-600						
Dimension	980*320*830mm						
Drum OD	ϕ600mm						
Axle OD	ϕ230mm						
Width	328mm						
Packing Dimension	1040*880*340mm						
Gross Weight	45KGS						
Net Weight	32KGS(Exclude drum)						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity 5600M	3100M	2000M	1400M	1000M	800M	620M	500M
Remarks	Parking brake ,wear-resistant rubber wheel,foldable						

Type	RCDD-380						
Dimension	380*305*492mm						
Drum OD	ϕ380mm						
Axle OD	ϕ235mm						
Width	190mm						
Packing Dimension	405*310*510mm Carton						
Gross Weight	5.4KGS						
Net Weight	4.0KGS						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	600M	400M	304M	223M	171M	135M	109M
Remarks	Plastic，Portable tie rod，No wear-resistant rubber wheel						

Type	RCDD-320						
Dimension	410*320*450mm						
Drum OD	Ø320mm						
Axle OD	Ø200mm						
Width	155mm						
Packing Dimension	420*330*480mm polywood case						
Gross Weight	13KGS						
Net Weight	9KGS						
Cable OD 3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity 600M	330M	200M	150M	100M	80M	60M	50M
Remarks	metal structure，Portable tie rod，wear-resistant rubber wheel						



Type		RCDD-550						
Dimension		645*545*605mm						
Drum OD		Ø550mm						
Axle OD		Ø120mm						
Width		310mm						
Packing Dimension								
Gross Weight								
Net Weight		19KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	6000M	3500M	2000M	1500M	800M			
Remarks		all-metal，No Portable tie rod，wear-resistant rubber wheel						

Type		RCDD-410						
Dimension		470*350*515mm						
Drum OD		Ø410mm						
Axle OD		Ø200mm						
Width		185mm						
Packing Dimension		475*365*520mm polywood case						
Gross Weight		16KGS						
Net Weight		10.5KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	1200M	650M	400M	300M	220M	170M	130M	110M
Remarks		metal structure，Portable tie rod，wear-resistant rubber wheel						

Type		RCDD-460-1						
Dimension		510*360*590mm						
Drum OD		Ø460mm						
Axle OD		Ø200mm						
Width		190mm						
Packing Dimension		525*370*595mm polywood case						
Gross Weight		19KGS						
Net Weight		12.5KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	1800M	1000M	600M	450M	320M	250M	200M	160M
Remarks		metal structure，Portable tie rod，wear-resistant rubber wheel						

Type		RCDD-460-2						
Dimension		510*470*590mm						
Drum OD		Ø460mm						
Axle OD		Ø200mm						
Width		295mm						
Packing Dimension		525*500*595mm polywood case						
Gross Weight		22KGS						
Net Weight		14.5KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	3600M	2000M	1200M	900M	650M	500M	400M	320M
Remarks		metal structure，Portable tie rod，wear-resistant rubber wheel						

Type		RCDD-230						
Dimension		410*440*400mm						
Drum OD		Ø230mm						
Axle OD		Ø72mm						
Width		200mm						
Packing Dimension		440*500*460mm polywood case						
Gross Weight		10KGS						
Net Weight		5KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	1800M	1000M	600M	450M	320M	250M	200M	160M
Remarks		Aluminium structure ,manpack type						



Type		RCDD-300						
Dimension		340*300*450mm						
Drum OD		Ø300mm						
Axle OD		Ø80mm						
Width		270mm						
Packing Dimension		385*365*520mm						
Gross Weight		9.7KGS						
Net Weight		5KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	1800M	1000M	600M	450M	320M	250M	200M	160M
Remarks		Aluminium structure ,manpack type						

Type		RCDD-500-1						
Dimension		930*220*640mm						
Drum OD		Ø500mm						
Axle OD		Ø230mm						
Width		328mm						
Packing Dimension		990*300*760mm						
Gross Weight		31KGS						
Net Weight		21KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	3600M	2000M	1200M	900M	650M	500M	400M	320M
Remarks		Parking brake ,foldable,metal structure						

Type		RCDD-500-2						
Dimension		870*170*700mm						
Drum OD		Ø500mm						
Axle OD		Ø230mm						
Width		328mm						
Packing Dimension		930*200*760mm						
Gross Weight		37KGS						
Net Weight		29KGS						
Cable OD	3.0mm	4.0mm	5.0mm	6.0mm	7.0mm	8.0mm	9.0mm	10mm
Capacity	3600M	2000M	1200M	900M	650M	500M	400M	320M
Remarks		Parking brake ,foldable,metal structure						